



09/827,889-041103

#11

Attorney Docket: 432580.0011

IN THE UNITED STATES. PATENT AND TRADEMARK OFFICE

In re Application of:

Claude Q.C. Hayes

Examiner:

Serial No.: 09/827,889

Group Art Unit: 1775

Filed: April 6, 2001

Confirmation No. 5565

For: Heat Absorbing Temperature Control Devices and Method

Commissioner for Patents
Washington, D.C. 20231

PRELIMINARY AMENDMENT

Sir:

Before commencing substantive examination of the above-referenced application, please
amend the application as follows:

RECEIVED

APR 15 2003

OFFICE OF PETITIONS

Claim Amendments

1 (original claim) An article of manufacture for the prevention of the increase of temperature in heat sensitive devices through the absorption of heat during heat generating conditions comprising:

bicarbonate salt in an amount sufficient to effect the required heat absorption; and means for supporting said bicarbonate salt, the physical characteristics of said means for supporting said sodium bicarbonate being defined by the heat absorbing application.

2 (currently amended). The article of manufacture according to Claim 1, wherein the bicarbonate salt is selected from the group consisting of Lithium Bicarbonate, Sodium Bicarbonate, Potassium Bicarbonate, Magnesium Bicarbonate, Calcium Bicarbonate, ~~Beryllium~~ Beryllium Bicarbonate, Aluminum Bicarbonate, Ammonium Bicarbonate and the mixtures thereof.

3 (original claim). The article of manufacture according to Claim 1, wherein the means for supporting said bicarbonate salt further comprises a retaining matrix, packaging, encapsulation, microencapsulation, enclosure or structure to form a heat absorbing surface, device or structure.

4 (original claim). The article of manufacture according to Claim 1, wherein the heat sensitive device is embedded within the bicarbonate salt.

5 (original claim). The article of manufacture according to Claim 1, wherein the heat sensitive device is surrounded by the bicarbonate salt.

6 (original claim). The article of manufacture according to Claim 1, wherein the means for supporting said bicarbonate salt is a closed container, within which said bicarbonate salt is located.

7 (original claim). The article of manufacture according to Claim 6, wherein said bicarbonate salt lines the inner wall of the closed container.

8 (original claim). The article of manufacture according to Claim 7, wherein said heat sensitive device is located within and spaced from said bicarbonate salt.

9 (original claim). The article of manufacture according to Claim 1, wherein said bicarbonate salt is adhered to a flexible substrate, said substrate being adaptable to the size and shape of said heat sensitive device.

10 (original claim). The article of manufacture according to Claim 1, wherein the means for supporting said bicarbonate salt is the bicarbonate salt itself.

Specification Amendments

With reference to the paragraph commencing at page 3, line 22 (of the Substitute Specification submitted herewith), please substitute the following amended paragraph:

Applicant has also addressed some of the PCM problems in his pending U.S. Patent Application Serial No. ~~08/183,199~~08/811,106, now U.S Patent No. ~~5,709,915~~5,709,914, the disclosure and contents of which are incorporated herein as if more fully set forth. Such application addresses the need for an improved recyclable endothermic/exothermic thermal storage method for use in many commercial and civilian applications, particularly for food, home and commercial packaging operations. In this application, improved CFEMs are disclosed, capable of being employed in a variety of commercial applications such as in the food industry where a need has arisen for heat retaining or heat insulating containers, packages and thermal storage devices.

With reference to the paragraph commencing at page 4, line 1 (of the Substitute Specification submitted herewith), please substitute the following amended paragraph:

However, the active agents suggested in Applicant's pending U.S. Patent Application Serial No. ~~08/183,199~~08/811,106, now U.S. Patent No. 5,709,914 are not useful in the present inventive heat absorbing devices, as they are concomitantly both endotherms and exotherms. i.e. first, they absorb heat and then they give off heat to the item in connection with which they are being used, for the purpose of maintaining it warm.

With reference to the paragraph commencing at page 4, line 15 (of the Substitute Specification submitted herewith), please substitute the following amended paragraph:

Another problem with the active agents of Applicant's, U.S. pending Patent Application Serial No. ~~08/183,199~~08/811,106, now U.S. Patent No. 5,709,914 and the

prior art PCMs is that they are not capable of absorbing more than 200 cal/gm. Thus, they can remove heat for only a short period of time relative to mass and only at temperatures not exceeding 326° F. Consequently, they are not effective for applications requiring cooling at very high temperatures and for long periods of time as would be needed, for example, in airplane and railroad crash recorders, missile electronics, spacecraft devices, power supplies, data recorders employed as aircraft and railroad components and combat devices, and in commercial uses such as oven sensors, fire walls, nuclear reactors, munitions' boxes, chemical containers, batteries and automobile exhaust systems.

Please add the following paragraphs immediately after the paragraph that concludes at page 7, line 3, but before the subheading "DETAILED DESCRIPTION," of the Substitute Specification submitted herewith:

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an illustrative schematic graph of the four phases of the heat absorption exhibited by Lithium Hydroxide and the phenomena observed during such phases, when Lithium Hydroxide is used as an endotherm, in accordance with the present invention;

FIG. 2 is an illustrative schematic graph of the four phases of the heat absorption exhibited by Sodium Hydroxide and the phenomena observed during such phases, when Sodium Hydroxide is used as an endotherm, in accordance with the present invention;

FIG. 3 is an illustrative schematic graph of at least two phases of the heat absorption exhibited by Aluminum Hydroxide and the phenomena observed

during such phases, when Aluminum Hydroxide is used as an endotherm, in accordance with the present invention;

FIG. 4 is an illustrative schematic graph of at least two phases of the heat absorption exhibited by Calcium Carbonate and the phenomena observed during such phases, when Calcium Carbonate is used as an endotherm, in accordance with the present invention;

FIG. 5 and FIG. 6 are graphs showing the natural delay in temperature rise for Lithium Formate and Lithium Acetate thermal decomposition reactions;

FIG. 7 and FIG. 8 are graphs showing the natural rise in temperature of conventional beryllium or wax heat sink when used with a flight data recorder, as compared to the same flight data recorder's thermal performance with a boric acid heat absorbing shield formed in accordance with the present invention; and

FIG. 9 is a graph showing the use of a hydrated salt, i.e., Magnesium Sulfate Heptahydrate, in accordance with the present invention.

With reference to the paragraph commencing at page 24, line 27 (of the Substitute Specification submitted herewith), please substitute the following amended paragraph:

In a preferred embodiment, however, of the heat absorbing device designed to protect from external heat, said device is placed adjacent ~~to the~~ to the heat sensitive device; thereafter insulation is wrapped or surrounded about the device and heat absorber and the entire package may be placed in a housing.

After the conclusion of the claims at page 30 of the Substitute Specification submitted herewith, please add the following Abstract:

ABSTRACT

The increase of temperature of heat sensitive devices during heat generating conditions is prevented through the absorption of heat, by providing a bicarbonate salt, such as lithium bicarbonate, sodium bicarbonate, potassium bicarbonate, magnesium bicarbonate, calcium bicarbonate, beryllium bicarbonate, aluminum bicarbonate, ammonium bicarbonate and mixtures thereof, in an amount sufficient to effect the required heat absorption. Where the heat generating conditions are generated by a heat generator, separate and distinct from the heat sensitive device, the bicarbonate salt may be supported in a position between the heat sensitive device and the heat generator. Where the heat sensitive device is itself the heat generator, the bicarbonate salt is in contact with the heat sensitive device, either directly or indirectly.

REMARKS

Applicant has amended the application to address editorial changes to the Substitute Specification submitted herewith, and to address formal requirements with respect to the application, e.g., through the inclusion of an Abstract and a Brief Description of the Drawings. Applicant respectfully submits that no new matter has been introduced to the application by way of the proposed amendments. Prompt action leading to an early Notice of Allowance is earnestly solicited.

Respectfully Submitted,



Basam E. Nabulsi

Reg. No. 31,645

Date: April 11, 2003

Cummings & Lockwood
Four Stamford Plaza
P.O. Box 120
Stamford, CT 06904-0120

CERTIFICATE OF EXPRESS MAILING

I hereby certify that this paper (along with any paper referred to as being attached or enclosed) is being deposited with the United States Postal Service on the date shown below with sufficient postage as Express Mail, Label No. EV167449403US in an envelope addressed to: Commissioner for Patents, BOX DAC, Washington, DC 20231

Date: 4/11/03

Name: Joan Simmons

Signature:

.StmLib1:1009367.1 04/11/03